Fujitsu recommends Windows 8 Pro.



Data Sheet Fujitsu ESPRIMO P400 Desktop PC

Your Immediately Available Office PC

Fujitsu All-round ESPRIMO PCs deliver high-quality computing for your office applications and projects at a very attractive price point. You can choose cost-optimized fixed configurations for immediate delivery. Alternatively, you can use configuration options to meet your specific hardware needs, while staying within your budget.

Intelligent performance

The ideal PC for the day-to-day challenges of office life

■ 3rd generation Intel® Core[™] i3, Core[™] i5, and Core[™] i7 processors

Designed and engineered in Germany

Outstanding quality and stable functions based on German production standards

■ The development, production and function tests are all under one roof in Germany

Immediate availability

Short waiting-times for fast purchase decisions - pre-configured and always available

■ Fast availability and adapted to constantly changing customer and market requirements





Components

Processor	Intel® Core™ i7-3770 processor (4 Cores / 8 Threads, 3.40 GHz, up to 3.9 GHz, 8 MB, Intel® HD Graphics 4000) *
	Intel® Core™ i5-3470 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 2500) *
	Intel® Core™ i5-3330 processor (4 Cores / 4 Threads, 3.00 GHz, up to 3.2 GHz, 6 MB, Intel® HD Graphics 2500)
	Intel® Core™ i3-3220 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2500)
	Intel® Pentium® processor G870 (2 Cores / 2 Threads, 3.10 GHz, 3 MB, Intel® HD Graphics)
	Intel® Pentium® processor G2120 (2 Cores / 2 Threads, 3.10 GHz, 3 MB, Intel® HD Graphics)
	Intel® Pentium® processor G2020 (2 Cores / 2 Threads, 2.90 GHz, 3 MB, Intel® HD Graphics)
	Intel® Celeron® processor G1610 (2 Cores / 2 Threads, 2.60 GHz, 2 MB, Intel® HD Graphics)
	*with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other
	variables)
Operating systems	
Operating system	Windows 8 Pro
	Windows 8
	Windows® 7 Professional 64-bit
	Windows® 7 Professional 32-bit
	Windows® 7 Home Premium 64-bit
	Windows® 7 Home Basic (EM) 32-bit
Operating system compatible	openSUSE Linux
	Windows Vista® (3rd gen Intel® Core™ processors are not supported) Windows® XP
Operating system potes	Windows® XP Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via
Operating system notes	http://support.ts.fujitsu.com
Mamaru madulas	· ·· · ·
Memory modules	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
Hard disk drives (internal)	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch
	HDD SATA III, 7200 rpm, 2000 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 250 GB, 3.5-inch
	HDD SATA II, 7200 rpm, 320 GB, 2.5-inch
Hard disk notes	Up to 20 GB of HDD space is reserved for system recovery
Graphics	NVIDIA® GeForce® 605 DisplayPort 1GB FH, 1 GB
•	DP to DVI-D (single link) Adapter Cable
	ATI Radeon® HD7350 1GB FH, 1 GB
Drives (optional)	BD Triple Writer SATA slim (tray)
	DVD-ROM
	DVD Super Multi
	MCR 24in1 & USB 3.0 front con., 3.5"
	MultiCard Reader 24in1 USB 2.0 3.5"
nterface add on cards/components (optional)	
	WLAN III, 802.11g/Draft-n (Windows only, dedicated regions only)
	USB 3.0 PCIe x1
	Gigabit Ethernet PCle x1, DS
	Dual serial card PCIe x1, powered
	Dual serial card PCle x1

Page 2 / 8 www.fujitsu.com/fts/ESPRIMO

Dage weit	ECDDIMO D/ 00
Base unit	ESPRIMO P400
Mainboard	
Mainboard type	D2990
Formfactor	μATX
Chipset	Intel® H61
Processor socket	LGA 1155
Processor quantity maximum	1
Memory slots	2 DIMM (DDR3)
Supported capacity RAM (max.)	16 GB
Memory frequency	1333 MHz
Memory notes	Dual channel support.
LAN	For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
LAN BIOS version	10/100/1000 MBit/s Realtek RTL 8111E
BIOS features	AMI Aptio 4.6
BIOS reacures	BIOS Flash EPROM update by software
	Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio codec	Realtek ALC663
Audio features	High Definition Audio
	riigii beliililloii Addio
I/O controller on board	
Serial ATA total	4
Controller functions	Serial ATA II (3 Gbit)
	NCQ
	AHCI
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	<u> </u>
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	8
USB 3.0 total	optional
USB front	2
USB rear	4
USB internal	2
VGA	1
DVI	1 (DVI-D)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Input device / components	
	Optical USB wheel mouse
Drive bays	
Drive bays total	5
3.5-inch internal bays	2
3.5-inch external bays	1
5.25-inch external bays	2
Slots	1 /210 /0.27: [] 5 []] . []
PCI-Express 2.0 x16	1 x (210 mm / 8.27 inch) Full height
PCI-Express x1	2 x (190 mm / 7.48 inch) Full height
Graphics on board	
Graphics brand name	Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU)
Shared video memory	up to 1759 MB

Page 3 / 8 www.fujitsu.com/fts/ESPRIMO

Graphics on board	
TFT resolution (VGA)	1024 x 768 pixel
	1280 x 1024 pixel
	1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel
	1600 x 1200 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel
Graphics features	Dual display support
•	DirectX® 10.1 or DirectX® 11 (depending on CPU)
	HDCP support
	Open GL® 3.3 (depending on CPU)
	Open CL® 1.1 (depending on CPU)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible
Graphics notes	Shared memory depending on main memory size and operating system
	Resolution (color depth up to 32 Bit/pixel)
	For TFT we recommend using 60Hz
	To 111 we recommend using our z
Electrical values	
	0-Watt mode with hard-off switch
Rated voltage range	200 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	200 V - 240 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	300 W
Monitor outlet	No
Power consumption	
Heat dissipation	
Heat dissipation notes	See white paper Energy Consumption
Noise for standard configuration (HDD,	ODD)
Noise emission	According to ISO9296
Related Processors for noise	Intel® Core™ i5 2400
	5.1 B/ 38 dB(A)
Noise Operation mode 1: ODD load (Blue angel requirement)	טע זע זעט טע זע זע. (א)עט טע זע זע.
Noise Operation mode 2: HDD load	4.4 B/ 29 dB(A)
(Blue angel requirement)	עט עט זוט דיד ביד עון אין טט עט זוע דיד ביד אין
Noise Operation mode 3: CPU 90% load	4.7 B/ 32 dB(A)
(Blue angel requirement)	און אַב פּטן אן אַב אַב אַנוּ אַב אַנוּ אַב אַנוּ אַב אַנוּ אַב אַנוּ אַנוּ אַנוּ אַנוּ אַנוּ אַנוּ אַנוּ אַנוּ
Noise Operation mode 4: High load	4.7 B/ 32 dB(A)
Noise Operation mode 5: Office	4.4 B/ 29 dB(A)
applications 2.0	1.1 6, 25 66 pt
Idle mode (Blue Angel requirement)	4.3 B/ 29 dB(A)
Noise notes	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)),
	Bystander position
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	175 x 425 x 353 mm
Difficultion (W X D X II)	
	6.89 x 16.74 x 13.9 inch
0 11 11	
Operating position	Vertical
Operating position Weight Weight (lbs)	

Page 4 / 8 www.fujitsu.com/fts/ESPRIMO

Dimensions / Weight / Environmental	
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 ℃ (50 - 95 °F)
Compliance	
Product	ESPRIMO P400
Model	
	MI4W-2990
Europe	CE CE
Global	RoHS (Restriction of hazardous substances)
	WEEE (Waste electrical and electronic equipment)
	Microsoft Operating Systems (HCT / HCL entry / WHQL)
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Additional Software	
Additional software (preinstalled)	Adobe® Reader®
	Norton Internet Security (incl. Firewall) 60 days version
	Win7: Fujitsu Recovery (Hard Disk Based Recovery)
	Win8: Microsoft Push Button Recovery (Hard Disk Based Recovery)
	Microsoft Office - buy license to activate the pre-installed Microsoft Office
Additional software (optional)	Recovery DVD for Windows®
	Drivers & Utilities DVD (DUDVD)
	CyberLink PowerDVD (BD/DVD playback software for Blu-ray Disc™)
	CyberLink PowerDVD (DVD playback software)
	Nero Essentials XL
Compatibility (references)	
	DMI 2.0
	PC 2001
	WMI 1.5
	USB 2.0
	SMBIOS
Manageability	
Manageability technology	DeskUpdate Driver management
	PXE 2.1 Boot code
	Wake up from S5 (off mode)
	WoL (Wake on LAN)
Security	
Physical Security	Kensington Lock support
	Eye for padlock
System and BIOS Security	Boot sector virus protection
	Control of external interfaces
User Security	User and supervisor BIOS password
	Access protection via external SmartCard reader (optional)
Packaging information	
Packaging dimension (mm)	500 x 290 x 540 mm
Packaging dimension (inch)	19.69 x 11.42 x 21.26 inch
Max. quantity / pallet	24
Material - Weight (g) Carton	1270 g
Material - Weight (lbs) Carton	2.8 lbs
Material - Weight (g) EPS / PS	160 g
Material - Weight (lbs) EPS / PS	0.35 lbs
Material - Weight (g) PE Material - Weight (lbs) PE	60 g 0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process
Warranty	
Standard Warranty	1 year
Service level	Bring-In / Onsite Service (depending on country)

Page 5 / 8

Warranty		
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty	
Maintenance and Support Services - the perfect extension		
Spare Parts availability	3 years	
Service Weblink	http://www.fujitsu.com/fts/services/support	

Recommended Accessories

Display E19-6 LED



The E19-6 LED combines comfortable ergonomics with best-in-class energy Order Code: saving technology like ECO operation mode.

BDL:TOP-E19-6-LED

Display E22W-6 LED



The E22W-6 LED combines comfortable ergonomics with best-in-class energy saving technology like ECO operation mode.

Order Code: BDL:TOP-E22W-6-LED

Display E19-6 LED



The Fujitsu Display E19-6 LED combines comfortable ergonomics with best- Order Code: in-class energy saving technology like ECO operation mode.

S26361-K1376-V160

Display E22W-6 LED



The Fujitsu Display E22W-6 LED combines comfortable ergonomics with best-in-class energy saving technology like ECO operation mode.

Order Code: S26361-K1377-V160

CELVIN® Drive D100



The CELVIN® Drive D100 is a highly reliable external storage device with a standard USB-interface for easy Plug & Play use with a notebook or PC. It is S26341-F103-L118 also easy to set up additional home network capacity by connecting it with dedicated routers or NAS devices.

Order Code:

SOUNDSYSTEM DS E2000 Air



The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.

Order Code: S26391-F7128-L600

WebCam 130 HD2



With the most advanced HD (High Definition / 720p) recording feature and Order Code: widescreen video format (16:9 and 16:10), WebCam 130 HD2 can capture up to 30 frame rate per second, close up to HD/720p quality video. Even more: 1-Click-Upload makes the video uploading to YouTube in a snap! With smart clip for notebook & LCD display it is easy to install on any device you want.

S26391-F7136-L5

Page 6 / 8 www.fujitsu.com/fts/ESPRIMO

HS E2000 Communicator Headset



The Fujitsu HS E2000 Communicator headset allows you to use your personal computer for Voice over IP (VoIP) in stereo audio quality. This premium headset is designed to provide superb audio quality and comfort for the telephony, internet chat, speech recognition, video conferencing and multimedia applications.

Order Code: S26391-F7139-L5

Keyboard KBPC PX ECO



Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC country specific variation) free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.

S26381-K341-L1** (**:

Keyboard KB900



The KB900 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB900 the ideal input device for any PC or Notebook user. If you accidently spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.

S26381-K560-L4** (**: Country specific variation)

Wireless Keyboard Set LX900



The Wireless Keyboard LX900 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set with offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption for security.

S26381-K564-L4** (**: Country specific variation)

Page 7 / 8 www.fujitsu.com/fts/ESPRIMO

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu ESPRIMO P400, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO P400, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at http://www.fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions Website: www.fujitsu.com/fts 2013-06-27 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

Copyright © Fujitsu Technology Solutions